

PACKING LEAKAGE MONITOR

ACI EnviroLine® Revolutionizes Monitoring Gas Leakage Rates

Installed in the packing vent line system, the ACI EnviroLine® packing leakage monitor provides a safe, reliable, and cost-effective means to monitor and quantify leakage rates from piston rod packing, as well as other vent systems.

The pre-packaged 12" x 12" modular-designed panel provides for easy installation via one inlet and one outlet connection. For systems where multiple measurement points are required, the monitor can be rack mounted with an appropriate number of valves.

Once properly connected, the system is ready to start monitoring with no additional requirements.

Differential Pressure Gauge

+/- 2% Accuracy
NACE Compliant
1,500 PSI MAWP

Nameplate

Graph for calculating actual flow rate

Stainless Steel Tubing & Fittings

0.25" OD x 0.035" Wall

Inlet & Outlet Connection

0.25" NPTF


Flow-Control Orifice

0.063" (typical) orifice diameter
Stainless steel

Filter

NOW AVAILABLE PRESSURE RELIEF VALVE

Limits distance piece back pressure
Standard models for 1.5, 2.0, 2.5, 3.5,
4.5, 6.0, or 7.5 psig (+/- 0.3 psig) settings



LEGENDS DON'T STOP. WE MAKE SURE OF IT.™

CALL +1 855-2COOPER | +1 740-435-0240
24/7 TECH SUPPORT: SUPPORT@COOPERSERVICES.COM
COOPERSERVICES.COM

